

## [Product Information]

# IMX511-AALJ

Ver.1.1

Diagonal 7.81 mm (Type 1/2.3) CMOS Image Sensor with Square Pixel for Color Cameras

---

### Description

The IMX511-AALJ is a diagonal 7.81 mm (Type 1/2.3) CMOS active pixel type stacked image sensor with a color square pixel array and approximately 25.69 M effective pixels. 12-bit digital output makes it possible to output the signals of approximately 25.69 M effective pixels with high definition for shooting still pictures. It operates with three power supply voltages : analog 2.8 V, digital 1.2 V, and 1.8 V for I/O interface and achieves low power consumption. Furthermore, it realizes 12-bit digital output for shooting high-speed and high-definition moving pictures by horizontal and vertical binning and subsampling readout. Realizing high-sensitivity, low dark current, this sensor also has an electronic shutter function with variable integration time. In addition, this product is designed for use in consumer use digital still camera and consumer use camcorder. When using this for another application, Sony Semiconductor Solutions Corporation does not guarantee the quality and reliability of the product. Therefore, don't use this for applications other than consumer use digital still camera and consumer use camcorder. In addition, individual specification change cannot be supported because this is a standard product. Consult your Sony Semiconductor Solutions Corporation sales representative if you have any questions.

---

### Features

- ◆ Back-illuminated and stacked CMOS image sensor
- ◆ Input clock frequency 72 MHz
- ◆ All-pixel readout mode
  - Various readout modes (\*)
- ◆ H driver, V driver and serial communication circuit on chip
- ◆ CDS/PGA on chip. Gain +27 dB (step pitch 0.2 dB)
- ◆ 10-bit/12-bit A/D conversion on chip
- ◆ Variable-speed shutter function (minimum unit: 1 horizontal sync signal period (1XHS))
- ◆ 8 / 4 Lane SLVS-EC output, support baud rates 4.608 / 2.304 Gbps
- ◆ Vertical and horizontal arbitrary cropping function
- ◆ Vertical and horizontal direction inverted readout mode
- ◆ Digital overlap (DOL) drive mode
- ◆ Multi Camera Function (chip ID up to six)
- ◆ Gyro data insertion function (Insert data from Gyro IC into frame data)
- ◆ R, G, B primary color mosaic filters on chip
- ◆ 148-pin high-precision ceramic package

\* Please refer to the datasheet for binning/subsampling details of readout modes.

Sony reserves the right to change products and specifications without prior notice.

Sony logo is registered trademark or trademark of Sony Group Corporation or its affiliates.

## Device Structure

◆ CMOS image sensor	
◆ Image size	Diagonal 7.81 mm (Type 1/2.3)
◆ Total number of pixels	5700 (H) × 5160 (V) approx. 29.41 M pixels
◆ Number of effective pixels	5215 (H) × 4927 (V) approx. 25.69 M pixels
◆ Number of active pixels	4927 (H) × 4927 (V) approx. 24.28 M pixels
◆ Chip size	9.280 mm (H) × 8.550 mm (V) (include scribe area)
◆ Unit cell size	1.12 μm (H) × 1.12 μm (V)
◆ Optical black	Vertical (V) direction : Front 40 pixels, rear 0 pixel
◆ Package	148 pin LGA

## Image Sensor Characteristics

(Tj = 60 °C)

Item		Value	Remarks
Sensitivity (F5.6)	Typ.	803 LSB	1/30 s integration
Saturation signal	Min.	4039 LSB	

## Basic Drive Mode

Drive mode	Number of active pixels	Max frame rate [frame/s]	Number of output bits [bit]
Readout mode 0	4927 (H) × 4927 (V) approx. 24.28 M pixels	47.47	12
Readout mode 1	4927 (H) × 4927 (V) approx. 24.28 M pixels	23.69	12
Readout mode 2	4927 (H) × 4927 (V) approx. 24.28 M pixels	63.23	12
Readout mode 3	4927 (H) × 4927 (V) approx. 24.28 M pixels	76.42	10
Readout mode 4	4927 (H) × 4927 (V) approx. 24.28 M pixels	38.13	10
Readout mode 6	2463 (H) × 2463 (V) approx. 6.07 M pixels	151.94	12
Readout mode 7	2463 (H) × 2463 (V) approx. 6.07 M pixels	75.67	12
Readout mode 8	1641 (H) × 1641 (V) approx. 2.69 M pixels	114.25	12
Readout mode 9	1641 (H) × 1641 (V) approx. 2.69 M pixels	226.22	12
Readout mode 10	1641 (H) × 1641 (V) approx. 2.69 M pixels	112.84	12
Readout mode 11	2463 (H) × 1641 (V) approx. 4.04 M pixels	226.22	10
Readout mode 12	1641 (H) × 985 (V) approx. 1.62 M pixels	368.09	12
Readout mode 13	1641 (H) × 985 (V) approx. 1.62 M pixels	183.34	12
Readout mode 14	1641 (H) × 245 (V) approx. 0.40 M pixels	1292.03	12
Readout mode 15	2463 (H) × 2463 (V) approx. 6.07 M pixels	151.70	10
Readout mode 16	2463 (H) × 2463 (V) approx. 6.07 M pixels	75.67	10
Readout mode 17	307 (H) × 245 (V) approx. 0.08 M pixels	1172.48	10